

X605e

Spectacular image quality, outstanding brightness and ultimate reliability



- **6000 lumens, XGA Resolution**
- **Installation flexibility – Lens shift, interchangeable lenses, off-axis short throw option**
- **Ultimate Control - Full support for Crestron, Extron, AMX, PJ-Link and Telnet LAN commands**
- **Advanced features – Wired Remote, Full 3D Support and DICOM simulation**

The X605e is a product designed exclusively for demanding professional applications.

XGA and 6000 lumens delivers bright crystal clear images with ultimate reliability, while 24/7 operation ensures that this is a projector on which you can rely.

The dust-sealed, filter free design prevents dust and dirt from affecting the system ensuring optimal image quality with minimal maintenance.



Specifications

Display/image	
Display technology	DLP
Resolution	XGA (1024x768)
Brightness	6.000 Lumens
Contrast ratio	2.000:1
Native aspect ratio	4:3
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - vertical	+/-30°
Horizontal scan rate	15.375 ~ 91.146 KHz
Vertical scan rate	24 ~ 85 (120Hz for 3D)Hz
Uniformity	85%
Screen size	Dependent on lens
Lamp info	
Light source type	Lamp
Lamp watts	365
Lamp life (hours)	3000 (Bright), 4000 (Eco)
Optical	
Throw ratio	Dependent on lens
Projection distance (m)	Dependent on lens
Lens shift	Vertical +50%, Horizontal: +/-10%
Lens options	Short: 0.8:1 (Fixed) Semi Short: 1.14 ~ 1.35 (1.18x zoom) Standard: 1.6 ~ 2.0:1 (1.25x zoom) Long: 2.0 ~ 3.0:1 (1.5x zoom) Extra Long: 3.11 ~ 5.18 (1.67x zoom)
Connectivity	
Connections	Inputs 1 x DVI-D, 1 x VGA (YPbPr/RGB), 1 x HDMI, 1 x Component, 1 x BNC, 1 x Composite video, 1 x S-Video, 1 x DisplayPort, 1 x Audio RCA L&R, 1 x Audio 3.5mm Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x 3D sync, 1 x USB-A power 1.5A Control 1 x 12V trigger, 1 x RS232, 1 x Wired remote, 1 x USB-B service, 1 x RJ45
General	
Noise level (typical)	34dB
PC compatibility	HD, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible
2D compatibility	PAL (625/576i/p), SECAM, NTSC (525/480i/p), HDTV (720p, 1080i/1080p)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar,Kensington Lock,Password protected interface
OSD / display languages	25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,German,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian, (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	Non-Operation: 5% ~ 95%, non-condensing Operating: 10% ~ 85%, non-condensing
Remote control	Wired backlit PRO AV remote
Heat dissipation	1.400BTU/hour
In the box	1.8m AC power cord, VGA cable, Batteries for remote, UM CD, Quick start card, Warranty card, WEEE card (For EMEA region only)
Networking	
LAN - control	Yes
LAN	Yes
Power	
Power supply	100V ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	370W
Power consumption (max)	480W
Weight and dimensions	
Net weight	8.6kg
Dimensions (W x D x H) mm	430 x 340 x 183

