

ZK750

High brightness professional 4K UHD laser projector



© Nordic Amusement Group

- **7,500 lumen 4K UHD DLP laser projector**
- **Five optional lenses**
- **Dust resistant – independently tested, IP6X certified for total reliability**
- **Pure engine video processing and colour matching**

Spectacular 4k UHD image quality, low maintenance and ultimate reliability

The ZK750 offers enhanced features such as MultiColor Laser (MCL) technology. Part of the DuraCore laser line up, it combines longer-lifetime light source and an independent IP rated dust certification for ultimate peace of mind.

Delivering an astonishing 30,000 hours, this projector achieves superior colour rendition through MultiColor laser technology producing visually striking lifelike images with exceptional detail.

Designed for even the most complex professional installations, the ZK750 offers five interchangeable lens options for ultimate flexibility.

It also offers portrait and 360-degree orientation support. Additionally, an HDBaseT™ input is included to simplify cabling requirements and reduce installation complexity, saving time and reducing costs.

Specifications

EAN: 5055387662957, Colour: Black

EAN: 5055387662964, Colour: RAL



Display/image

Display technology	DLP™
Resolution	UHD (3840x2160)
Brightness	7,500 lumens
ANSI brightness	7,000
Contrast ratio	5,000:1
Contrast ratio - dynamic	2,000,000:1
Contrast ratio - full on/off	1,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	16:9
Keystone correction - horizontal	+/- 20°
Keystone correction - vertical	+/- 20°
Screen size	Dependent on lens

Lamp info

Light source type	DuraCore MultiColor Laser
LASER life	30,000 hours

Optical

Throw ratio	Dependent on lens
Projection distance (m)	Dependent on lens
Lens options	A25 0.85~1.02, A26 1.20~1.73, A20 1.70~2.12, A21 2.12~2.83, A22 2.83~5.66, A23 5.66~10.18

Connectivity

Connections	Inputs 2 x HDMI 2.0, 1 x DisplayPort, 1 x HDBaseT, 1 x 3G-SDI, 1 x 3D sync, 1 x Wired remote Outputs 1 x HDMI, 1 x 3D sync, 1 x Wired remote Control 1 x RS232, 1 x 12V trigger, 1 x USB-A service, 1 x RJ45
-------------	---

LAN - wireless networking

No

General

Noise level (typical)	32dB
Noise level (max)	36dB
3D	Full 3D
Security	Security bar
IP rating	IP6X
OSD / display languages	11 languages: Dutch, English, French, German, Indonesian, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish
24/7 operation	Yes
360° operation	Yes
Remote control	Backlit ProAV remote
Heat dissipation	3,224BTU/hour
In the box	TBC

Networking

LAN - control	Yes
LAN - wireless networking	No
LAN	Yes

Power

Power supply	AC 100 – 240 V @ 50/60 Hz
Power consumption (standby)	0.5W
Power consumption (min)	530W
Power consumption (max)	1,035W

Weight and dimensions

Dimensions (W x D x H) mm	600 x 520 x 219
Gross weight	46.5 kg
Net weight	33.1 kg

