

# UHD60

A greater sense of depth and realism in every scene

---



- **4K UHD resolution and HDR compatible**
- **Amazing colour - accurate Rec.709 colours, 3000 ANSI lumens**
- **Easy connectivity - HDMI 2.0, HDCP 2.2, S/PDIF, 2x 4W speakers**
- **Easy installation - vertical lens shift**

TV, gaming and movie fans can now enjoy impressive 4K cinema quality images in their own home with the Optoma UHD60. Incorporating Ultra HD 4K resolution it brings content to life with thrilling detail, colour and contrast for a stunningly immersive experience.

Packed with the latest technology and features, the stylish UHD60 boasts High Dynamic Range (HDR) compatibility, HDCP 2.2 support and includes an integrated speaker that provides powerful sound. Bright 3000 lumen images and easy set-up means you can enjoy life-like big-screen entertainment in any living space.

## Specifications

<b>Display/image</b>	
Display technology	DLP
Resolution	UHD (3840x2160)
Brightness	3,000 lumens
Contrast ratio	1,000,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Horizontal scan rate	31 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	85%
Screen size	0.67m - 7.68m (26.45in - 302.2in)(Diagonal)
<b>Lamp info</b>	
Light source	Lamp
Lamp watts	240
Lamp life (hours)	4000 (Bright), 15000 (Dynamic), 10000 (Eco)
<b>Optical</b>	
Throw ratio	1.39:1 - 2.22:1
Projection distance (m)	1.3m - 9.3m
Zoom	1.6
Zoom type	Manual
Focal length (mm)	20.91 ~ 32.62
Lens shift	Vertical +15, %
Native offset	100%
<b>Connectivity</b>	
Connections	<b>Inputs</b> 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support + MHL, 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A service <b>Outputs</b> 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x 12V trigger <b>Control</b> 1 x RS232, 1 x RJ45
<b>General</b>	
Noise level (typical)	25dB
PC compatibility	UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Backlit home remote
Speaker count	2
Watts per speaker	4W
In the box	AC power cord, remote control, 2x AA batteries, lens cap, basic user manual
<b>Networking</b>	
LAN - control	Yes
<b>Power</b>	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (max)	305W
<b>Weight and dimensions</b>	
Net weight	7.8kg
Dimensions (W x D x H) (mm)	498 x 331 x 141

