

ZU720T

World's first fixed lens 7500 lumen WUXGA laser projector



- **7500 lumen fixed lens - Ultra bright for installations where high brightness is required**
- **Full lens shift - Motorised lens shift for simple set up**
- **Large zoom range - 1.8x zoom expands placement opportunities**
- **30,000 hours laser light source - Little to no maintenance for up to 30,000 hours**

The ZU720T is the world's first fixed lens 7500 lumen WUXGA laser projector. Delivering high brightness along with 4K and HDR compatibility, the ZU720T offers low maintenance and extremely long-life DuraCore laser projection technology.

This high-spec projector features a large 1.8x zoom and 1.4~2.5:1 throw ratio, full lens shift and built-in dual 10W speakers for unrivalled flexibility.

Suitable for a wide variety of applications, the ZU720T is perfect for large venues, classrooms, lecture theatres, museums and houses of worship.

The added flexibility of HDBaseT and LAN make this projector an affordable fit and forget solution.

Specifications

Display/image	
Display technology	DLP
Resolution	WUXGA (1920x1200)
Brightness	7,500 lumens
Contrast ratio - dynamic	1,000,000:1
Contrast ratio - full on/off	1,100:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Screen size	1.02m ~ 7.62m (40" ~ 300") diagonal
Lamp info	
Light source type	DuraCore Laser
LASER life	30,000 hours
Optical	
Throw ratio	1.4:1 ~ 2.5:1
Projection distance (m)	1.2m - 16.5m
Zoom	1.8
Zoom type	Manual
Focal length (mm)	20.68~37.23
Lens shift	Vertical: +/-55%, Horizontal: +/-25%
Lens shift	Yes - (downloads_link)
Connectivity	
Connections	<p>Inputs 1 x HDMI 1.4a 3D support, 1 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm, 1 x HDBaseT, 1 x 3D sync</p> <p>Outputs 1 x HDMI 1.4a 3D support, 1 x Audio 3.5mm, 1 x 3D sync, 2 x USB-A power 1.5A</p> <p>Control 1 x 12V trigger, 1 x USB-B service, 1 x RJ45, 1 x Wired remote, 1 x RS232</p>
General	
Noise level (typical)	27dB
Noise level (max)	31dB
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP5x
OSD / display languages	23 languages: Arabic, Czech, Danish, Dutch, English, Farsi, French, German, Greek, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	10% to 85% Humidity, non-condensing
Remote control	Backlit ProAV remote
Heat dissipation	2.013BTU/hour
Speaker count	2
Watts per speaker	10W
Networking	
LAN	Yes
Power	
Power consumption (standby)	0.5W
Power consumption (min)	370W
Power consumption (max)	590W
Weight and dimensions	
Net weight	12.7kg
Dimensions (W x D x H) mm	484 x 178.5 x 376

