

WHD200

Wireless HDMI sender and receiver



- **Full HD wireless video up to 1080p60Hz (Full 3D support)**
- **Easy setup with auto detection - Plug & Play**
- **20m Range (in room)**
- **2x HDMI 1.4a 3D inputs, 1x HDMI 1.4a 3D output**

Effortlessly stream Full HD 1080p 3D content to your projector or TV wirelessly. Eliminating the hassle and extra cost of installing long cables. The WHD200 allows you to connect to any HDMI device such as a Blu-ray player, digital set-top box, games console, laptop or AV receiver.

For added convenience, two input devices can be simultaneously connected to the WHD200. A second display can also be connected using the included HDMI out port, which means set-up is simple for a super-sized Full HD experience.

Note: Multiple receivers cannot be used Up to three devices can be used in one room

Receiver dimensions - 95 x 95 x 34 mm Transmitter dimensions - 182 x 92 x 31 mm

System latency - Ultra Low <1ms Operating temp - 0 ~ 40°C Audio Input Support - Up to 6 Mbps AC-3 and DTS

Specifications

General

| | |
|---------------------------------------|---|
| Net weight | 0.329kg |
| Operating temperature (max) | 40°C |
| Wireless - range | 20m |
| Wireless - antenna | Omni-directional High Performance Internal Antennas |
| Wireless - operating frequency | 4.9 ~ 5.9GHz |
| Wireless - technology | WHDI |
| Power supply | 100 ~ 240V (5V DC) |
| Connections | Inputs 2 x HDMI 1.4a 3D support, 1 x DC, 1 x mini USB Outputs 2 x HDMI 1.4a 3D support |
| 3D compatibility | Frame-pack: 1080p24, 720p50/60 Side-by-Side:1080i50/60, 720p50/60 Over-Under: 1080p24, 720p50/60 |
| 2D compatibility | 1080p24, 1080p50, 1080p60 1080i50, 1080i60 720p50, 720p60, 576p, 480p |
| In the box | Quick start guide 2* Power adapters 2* HDMI cables Remote inc 2* AAA batteries IR repeater |

