

UHZ67

Eco-friendly compact high brightness 4K UHD laser projector



- **Incredible True 4K UHD resolution and laser technology - HDR and HLG compatible**
- **Lights on viewing - bright 4300 lumens - Perfect for big screen home entertainment and immersive gaming**
- **Optoma Smart Control App - Control this projector and make quick and easy image adjustments all from your mobile device**
- **Low input lag - Gaming mode supports 1080p 240Hz at 6.5ms and 4K 60Hz at 20ms for responsive gaming and viewing**



The UHZ67 is one of Optoma's most compact and hassle-free 4K UHD DuraCore laser projectors to date. Designed for maintenance-free continuous operation, this 4300-lumen projector delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.¹

Use Optoma's latest Smart Control App to make quick adjustments to your setup and take advantage of low latency gaming mode for lighting quick response times.

Specifications

EAN: 5055387669727, Colour: Black



Display/image

Display technology	DLP®
Resolution	UHD (3840x2160)
Brightness	4,300 lumens
Contrast ratio	500,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9,16:10,21:9,32:9
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Displayable colours (millions)	1073.4
Horizontal scan rate	15 ~ 150Khz
Vertical scan rate	24 ~ 240Hz
Uniformity	80%
Screen size	0.66m ~ 7.7m (26" ~ 303") diagonal

Lamp info

Light source type	Laser
LASER life	30,000 hours

Optical

Throw ratio	1.4:1 ~ 2.24:1
Projection distance (m)	1.3m - 9.4m
Zoom	1.6
Zoom type	Manual
Focal length (mm)	20.91 ~ 32.62
Native offset	116%

Connectivity

Connections	Inputs 1 x HDMI 2.0, 1 x HDMI 2.0 (eARC) Outputs 1 x Audio 3.5mm, 2 x USB-A power 1.5A Control 1 x RJ45, 1 x RS232, 1 x 12V trigger, 1 x 3D sync
-------------	---

General

Noise level (min)	29dB
Noise level (max)	35dB
PC compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D)
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft
Speaker count	1
Watts per speaker	15W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Input lag	4.40ms

Power

Power supply	External power supply, 100V ~ 240V, 50-60Hz
Power consumption (standby)	<0.5W
Power consumption (min)	124W
Power consumption (max)	178W

Weight and dimensions

Dimensions (W x D x H) mm	274 x 216 x 114
Gross weight	4.3 kg
Net weight	2.9 kg